

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

THIS PAGE BLANK (USPTO)



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : H04Q 7/00	A2	(11) International Publication Number: WO 00/19742 (43) International Publication Date: 6 April 2000 (06.04.00)
(21) International Application Number: PCT/US99/23002 (22) International Filing Date: 1 October 1999 (01.10.99) (30) Priority Data: 09/164,554 1 October 1998 (01.10.98) US (71)(72) Applicants and Inventors: LE, Khiem [US/US]; 607 St-Andrews Place, Coppell, TX 75019 (US). HSU, Liangchi, Alan [-/US]; 2614 Tillman Drive, Arlington, TX 76006 (US). LANSISALMI, Atte [FI/FI]; Otakallio 4 A 10, FIN-02150 Espoo (FI). (74) Agent: LYNCH, David, W.; Altera Law Group, 10749 Bren Road East, Minneapolis, MN 55343 (US).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>Without international search report and to be republished upon receipt of that report.</i>
(54) Title: METHOD AND APPARATUS FOR PROVIDING OVERLAY TO SUPPORT POST-SECOND GENERATION CELLULAR SERVICES (57) Abstract An overlay to an existing cellular switching structure to provide post-second generation services without the need to make modifications or updates to the existing infrastructure is disclosed. The overlay preserves second generation switching while providing post-second generation services. The overlay includes a post-second generation infrastructure for providing processing of post-second generation communication services, a first interface, coupled to the post-second generation infrastructure, for providing an access interface to a base station subsystem and processing base station subsystem signaling based upon a type of service and a type of call flow associated with the received signaling from the base station subsystem, and a second interface, coupled to the post-second generation infrastructure, for providing an inter-system interface to a signaling network and processing inter-system signaling between the signaling network, the first interface, the existing switching infrastructure and the post-second generation infrastructure. The first interface comprises an access interface manager, the access interface manager outputting access interface signaling based on base station subsystem signaling received from the base station subsystem according to a type of service and a type of call flow associated with the received base station subsystem signaling. The access interface manager further comprises a base station subsystem manager and a protocol interworking manager and the second interface includes an inter-system interface manager. The post-second generation infrastructure includes a general packet radio service system including a packet handoff manager, a serving general packet radio service support node, and a gateway general packet radio service support node.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

METHOD AND APPARATUS FOR PROVIDING OVERLAY TO SUPPORT POST-SECOND GENERATION CELLULAR SERVICES

BACKGROUND OF THE INVENTION

1. Field of the Invention.

5 This invention relates in general to cellular communication systems, and more particularly to an overlay to an existing cellular switching structure to provide post-second generation services without the need to make modifications or updates to the existing infrastructure.

2. Description of Related Art.

10 The demand by consumers all over the world for mobile communications continues to expand at a rapid pace and will continue to do so for at least the next decade. Over 100 million people were using a mobile service by the end of 1995, and that number is expected to grow to 300 million by the year 2000. Several factors are contributing to the exciting
15 growth in the telecommunications industry. For example, a combination of technology and competition bring more value to consumers. Phones are smaller, lighter, had a longer battery life, and are affordable now for the mass market. Operators are providing excellent voice quality, innovative services, and roaming across the country or world. Most important, mobility
20 is becoming less expensive for people to use. Around the world, as well as in the United States, governments are licensing additional spectrum for new operators to compete with traditional cellular operators. Competition brings innovation, new services, and lower prices for consumers.

For cellular telephony to continue its spectacular growth, it must handle more subscribers per base station and higher-bandwidth services. Toward that end, the industry's third technology generation (3G) is envisioned as a move beyond voice-only terminals to information
5 communicators that will pass images and data.

Europe's Universal Mobile Telecommunications Standard (UMTS) is the follow-on to the second-generation Global System for Mobile communications (GSM) digital cellular standard. The Universal Mobile Telecommunications System (UMTS) is intended to provide a worldwide
10 standard for personal mobile communications with the mass-market appeal and quality of wireline services. Over recent years, digital cellular technologies, such as GSM, have led the way towards personal communications, making mobile communications available to millions of users all around the world at reasonable cost. But to match the UMTS
15 vision, a communications system must include support for flexible bearer and bandwidth-on-demand services for local (indoor) environments and for wide area coverage; a variety of mixed traffic types and relevant charging capability for mobile multimedia applications; customized services, service creation environments and service flexibility using, for example, intelligent
20 network (IN) tools; and wideband wireless local loop (WLL) enhancement to the fixed network.

However, the wireless market in the United States is not as settled. For example, there are efforts to pursue a third-generation mobile standard based on the CDMA-One air interface.

Accordingly, any post-second generation air interface, e.g., a post-second generation (3G) air interface, must provide high speed packet data and second generation services as a subset of the post-second generation services. Herein post-second generation will be used to referred to any type
5 of entity that is developed and implemented after the second generation entities.

As operators are forced to implement post-second generation infrastructure, second generation switching infrastructure must be modified or replaced to support the new services such as high speed packet data.
10 Still, the framework of the existing infrastructure may not be optimal for support of post-second generation services, and practically, the operator may have to stay with the same switch supplier.

It can be seen that there is a need for a method and system that preserves second generation switching while providing post-second
15 generation services.

It can also be seen that there is a need for an overlay to existing switching infrastructure to provide post-second generation services without requiring modifications or updating to the existing infrastructure.

SUMMARY OF THE INVENTION

To overcome the limitations in the prior art described above, and to overcome other limitations that will become apparent upon reading and understanding the present specification, the present invention discloses an
5 overlay to an existing cellular switching structure to provide post-second generation services without the need to make modifications or updates to the existing infrastructure.

The present invention solves the above-described problems by providing a method and system that preserves second generation switching
10 while providing post-second generation services.

A system in accordance with the principles of the present invention includes a post-second generation infrastructure for providing processing of post-second generation communication services, a first interface manager, coupled to the post-second generation infrastructure, for providing an
15 access interface to a base station subsystem and processing base station subsystem signaling based upon a type of service and a type of call flow associated with the received signaling from the base station subsystem, and a second interface manager, coupled to the post-second generation infrastructure, for providing an inter-system interface to a signaling network
20 and processing inter-system signaling between the signaling network, the first interface manager, the existing switching infrastructure and the post-second generation infrastructure.

Other embodiments of a system in accordance with the principles of the invention may include alternative or optional additional aspects. One

such aspect of the present invention is that the first interface manager comprises an access interface manager, the access interface manager outputting access interface signaling based on base station subsystem signaling received from the base station subsystem according to a type of service and a type of call flow associated with the received base station subsystem signaling.

Another aspect of the present invention is that the access interface manager further comprises a base station subsystem manager and a protocol interworking manager.

Another aspect of the present invention is that the second interface manager further comprises an inter-system interface manager.

Yet another aspect of the present invention is that the post-second generation infrastructure further comprises a general packet radio service system including a packet handoff manager and a serving general packet radio service support node.

Another aspect of the present invention is that the post-second generation infrastructure further comprises a gateway general packet radio service support node coupled to the serving general packet radio service support node.

Another aspect of the present invention is that the inter-system signaling comprises access interface signaling for the access interface manager, post-second generation signaling for the post-second generation switching infrastructure, existing switch signaling for the existing switching infrastructure, and signaling network signaling for the signaling network.

Another aspect of the present invention is that the existing switching infrastructure comprises a mobile switching center and a visitor location register.

Still another aspect of the present invention is that the existing
5 switching infrastructure further comprises a home location register coupled to the second interface.

Another aspect of the present invention is that the home location register provides administrative information and the current location of each registered subscriber accessing the existing switching infrastructure in the
10 network.

Another aspect of the present invention is that the call flows comprise, among others, registration signal flows, mobile origination call flows and hard handoff signal flows.

These and various other advantages and features of novelty which
15 characterize the invention are pointed out with particularity in the claims annexed hereto and form a part hereof. However, for a better understanding of the invention, its advantages, and the objects obtained by its use, reference should be made to the drawings which form a further part hereof, and to accompanying descriptive matter, in which there are illustrated and described
20 specific examples of an apparatus in accordance with the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

Referring now to the drawings in which like reference numbers represent corresponding parts throughout:

Fig. 1 shows an existing second generation cellular architecture;

5 Fig. 2 shows the overview of the infrastructure and overlay according to the present invention;

Fig. 3 illustrates a more detailed block diagram of an overlay system according to the present invention;

10 Fig. 4 illustrates inter-MSC/VLR Registration flow according to the present invention;

Fig. 5 illustrates the flow of a mobile originated packet data according to the present invention;

Fig. 6 illustrates the high level flow of a hard handoff according to the present invention;

15 Fig. 7 illustrates the Handoff Required and FACDIR2 messaging which is used in Fig. 6 according to the present invention; and

Fig. 8 illustrates the start of the GPRS handoff which is used in Fig. 6 according to the present invention.

DETAILED DESCRIPTION OF THE INVENTION

In the following description of the exemplary embodiment, reference is made to the accompanying drawings which form a part hereof, and in which is shown by way of illustration the specific embodiment in which the invention may be practiced. It is to be understood that other embodiments may be utilized as structural changes may be made without departing from the scope of the present invention.

The present invention provides a signaling scheme that includes an overlay to an existing switching infrastructure to provide post-second generation services, without requiring modifications or updating to the existing infrastructure. The overlay scheme according to the present invention involves two primary concepts. The first concept is to combine/split the signaling to/from other switches and to/from the Base Station. The second concept is for the overlay to intercept the signaling between the existing switch and the Base Station, and between the existing switch and the other switches. For clarity purposes only, the present invention will be described with reference to the use of the second generation (2G) IS-95 CDMA air interface as the existing switching infrastructure. However, those skilled in the art will recognize that the present invention is not meant to be limited to a particular existing infrastructure, but preserves the investment in the existing switching infrastructure by continuing to use it for existing services. Furthermore, the overlay can be independently optimized for new services, and does not require a change in the existing second generation infrastructure.

Fig. 1 shows an existing second generation cellular architecture 100.

In Fig. 1, the existing second generation cellular structure includes a base station subsystem (BSS) 110 and the Mobile Switching Center/Visitor

Location Register (MSC/VLR) 120. The central component of a network

5 subsystem is the Mobile Switching Center (MSC). The MSC acts like a normal switching node of the Public Switched Telephone Network (PSTN) or Integrated Services Digital Network (ISDN), and additionally provides all the functionality needed to handle a mobile subscriber, such as registration,

authentication, location updating, handovers/handoffs, and call routing to a

10 roaming subscriber. The VLR contains selected administrative information from a Home Location Register (HLR), necessary for call control and

provision of the subscribed services, for each mobile station (MS) 130

currently located in the geographical area controlled by the VLR. Although each functional entity can be implemented as an independent unit,

15 manufacturers of switching equipment generally implement the VLR together with the MSC, so that the geographical area controlled by the MSC corresponds to that controlled by the VLR, thus simplifying the signaling required.

The switching system interacts with the rest of the world through two

20 interfaces. First, the BSS 110 interacts with the MSC/VLR 120 via the

Access Interface 140, e.g., IS-634. Next, the MSC/VLR 120 interacts with

the Signaling Network 150 via an Inter-system Interface 160, e.g., IS-41.

Finally, the MS 130 interacts with the BSS 110 via an air interface 170, e.g., IS-95.

Fig. 2 shows the overview of the infrastructure and overlay 200. The new mobile station (MS) 210 and new base station subsystem (BSS) 212 support the new post-second generation air interface 214. The existing infrastructure provides second generation services, while the post-second generation infrastructure 230 is designed to support new services in accordance with the new air interface 214. The second generation services could be speech or low speed data service and post-second generation services could be high speed data services or multimedia applications.

The present invention provides an overlay 240 that includes the post-second generation infrastructure 230 as shown in Fig. 2. Two Interface Managers 242, 244 provide functions to combine and split signaling to/from the new BSS 212 and signaling to/from other (switching) systems in the signaling network 260 respectively. By doing so, the existing system 220 is able to provide existing second generation services, which usually are a subset of post-second generation services provided by the post-second generation infrastructure 230. Furthermore, the post-second generation infrastructure 230 for new services can be independently optimized for post-second generation services without changing the existing system 220.

As mentioned above, this invention considers the case of second generation IS-95 CDMA for concreteness, but without loss of generality, although the ideas presented here are applicable to other cases. As IS-95 air interface evolves to a post-second generation interface, i.e. a 3G CDMA air interface, with high speed packet data as the main service driver, the infrastructure is expected to be impacted as follows. The radio base station

(BS) infrastructure will likely have to be replaced by a new one (i.e. CDMA 3G BSS) 212, due to the extensive changes to the radio specifications. The switching infrastructure will also have to be modified to support high speed packet data, although a replacement is less likely. The present invention

5 defines a scheme that enables the addition of an overlay 240 that is optimized for high speed packet data, without requiring changes to the second generation switching infrastructure 220. When it is available, a post-second generation radio base station infrastructure 230 with a standardized access interface can be connected to the second generation switching

10 infrastructure through an Access Interface Manager 242. General Packet Radio Service (GPRS) infrastructure is used in this invention as an example of the post-second generation infrastructure for new services, i.e. GPRS is used to provide high speed packet data for post-second generation services. However, those skilled in the art will recognize that the concept embodied by

15 the present invention can be applied to other systems.

Fig. 2 shows the addition of an overlay 240 on top of the existing switching infrastructure 220 to support post-second generation services. The overlay 240 includes an infrastructure for new services 230, and two interface managers: the Access Interface Manager (AIM) 242, and the Inter-

20 system Interface Manager (IIM) 244. The interface managers 242, 244 perform the appropriate protocol conversions and interworking so that the existing switching infrastructure 220 does not have to be modified, and can still be used for second generation services, which are a subset of the post-second generation services. In particular, the existing switch 220 still sees a

second generation access interface 246 and a second generation inter-system interface 248. The infrastructure investment is thus preserved. The post-second generation BSS 212 sees a post-second generation access interface 250. A standard post-second generation BSS 212 can thus be
5 used. The other post-second generation systems from the signaling network 260 see a post-second generation inter-system interface 252 when they interact with the overlay system 240 and the existing infrastructure 220, thus enabling transparent interoperability. Finally, the protocol conversion/interworking done by the interface managers 242, 244 include
10 two key features: signaling splitting/combining, and signaling interception. Accordingly, the AIM 242 and IIM 244 provide signaling to and from the existing switching system 220, the post-second generation infrastructure 230 and each other, i.e., via inter-manager signaling interface 254.

The AIM 242 provides access interface signaling including the
15 signaling from the AIM 242 to the existing switching system 220 via the second generation access interface 246, signaling 270 from the AIM 242 to the post-second generation infrastructure 230 and inter-manager signaling from the AIM 242 to the IIM 244 via inter-manager interface 254. The IIM processes inter-system signaling including the inter-manager signaling via
20 the inter-manager interface 254, post-second generation signaling 272 for the post-second generation switching infrastructure 230, existing switch signaling via second generation inter-system interface 248, and signaling network signaling for the signaling network via post-second generation inter-system interface 252.

The post-second generation infrastructure 250 for new services can be optimized for new services, independently of the second generation infrastructure 220. While, the existing CDMA system is only suitable for speech and low speed data services, i.e., 9.6 Kbps or 14.4 Kbps maximum, the post-second generation of CDMA is expected to offer high rate services, e.g., 384 Kbps, or very high rate services, e.g., 2 Mbps. Further, while the standardization process of air interface and network for the post-second generation is still underway, the standardization of General Packet Radio Service (GPRS) is almost finalized, and GPRS high speed packet data service is expected to be in service in the near future. Accordingly, the present invention may be applied to the case of overlaying CDMA system and GPRS systems to provide services of speech and high speed packet data in a more timely manner. Accordingly, the more specific explanation of an overlay 240 according to the present invention will be described with reference to a GPRS/CDMA system. Those skilled in the art will recognize that the present invention is not meant to be limited to a GPRS/CDMA system.

Fig. 3 illustrates a more detailed block diagram of an overlay system according to the present invention. In Fig. 3, the 3G CDMA air interface 310 is used between the MS 312 and BSS 314. The existing system includes MSC/VLR 320 and a HLR 382. The HLR 382 contains all the administrative information of each second generation registered subscriber accessing the existing switching infrastructure 320 in the network, along with the current location of a MS 312 requesting second generation mobile services. The

post-second generation infrastructure 330 for new services contains a Packet Handoff (HO) Manager 332 and a Serving GPRS Support Node (SGSN) 334. A Gateway GPRS Support Node (GGSN) 336 is also provided for the GPRS. The Serving GPRS Support Node (SGSN) 334, which is at
5 the same hierarchical level as the MSC 320, keeps track of the individual MS 312 location and performs security functions and access control for packet data services. The GGSN 336 provides interworking with external packet-switched networks, and is connected with SGSNs 334 via an IP-based GPRS backbone network 338.

10 The overlay includes functional entities of an Access Interface Manager (AIM) 340 including a BSS manager 342 and a Protocol Interworking (IW) 342, an Inter-System Interface Manager 350 including a System Manager 352, and a Packet Handoff (HO) Manager 332. In this example, the G-CDMA 360 is the system combining the new air interface
15 310, the existing infrastructure 320, the post-second generation infrastructure 330, and the above-mentioned components of the overlay system. The G-CDMA system 360 is connected to a Signaling System 7 (SS7) signaling network 370. The SS7 signaling network 370 is connected to other systems, such as other G-CDMA systems 380 or a regular, second
20 generation CDMA system 382.

The handling of call flows illustrates the operation, as well as the importance, of the present invention. The present invention may handle all call flows including but not limited to Registration, Mobile Origination Call,

and Hard Handoff (speech and packet data). Figs. 4-6 illustrates examples of call flows according to the present invention.

Fig. 4 illustrates inter-MSC/VLR Registration 400 according to the present invention. In Fig. 4, the access interface manager (AIM) is the BSS manager 410 and Protocol IW 412. The inter-system interface manager (IIM) is the system manager 416. At step 1 418, the MS 440 sends the Registration over the air interface to the BSS 442 indicating the type of registration. At step 2 420, the BSS 442 sends a corresponding access interface message to the BSS manager. At step 3, the BSS manager will routinely distribute a first access interface Registration message 422 (i.e., LA Updating Request) to the MSC/VLR 450 and a second access interface Registration message 424 (i.e., LA Updating Request) to the system manager 416. The message 424 to the system manager 416 will include the Location Area Identity (LAId) of the cell that the MS 440 is registering in. The BSS manager 410 will wait for a response from the system manager 416 to determine whether a GPRS procedure is needed. The system manager 416 will check whether it recognizes this MS 440 or not.

The system manager 416 combines messages 424 at step 3 and the Registration Notification (REGNOT) message at step 4 426 into the REGNOT message at step 5 428. If the MS 440 is not known, the inter-MSC/VLR Registration continues, and the system manager 416 waits to see the HLR updating via step 6 430 for this user. If MS 440 is not known to the MSC/VLR 450, and a Temporary Mobile Subscriber Identification (TMSI)

was used as the Mobile Subscriber Identification (MSId), the IMSI is retrieved. If the MS is known, it is a case of intra-MSC/VLR registration.

In steps 4 426, 5 428, 6 430, and 8 434, the messages are regular IS-41 HLR updating and registration cancellation messages. In step 6 430, the message also carries the GPRS addition in the profile, if one exists, but the system manager 416 will remove the GPRS addition. Message 8 434 contains a pure IS-41 profile. In step 7 432, if the profile has GPRS addition, i.e., the MS is G-CDMA capable, the new G-CDMA registration message is sent to the BSS manager 410. The message in step 7 432 contains a new parameter called the `inter_ind`, which indicates whether the procedure is inter or intra-SGSN. The system manager 416 will indicate "inter SGSN" if the MS 440 is unknown, or known but the LAId indicates another SGSN. The system manager 416 will indicate "intra SGSN" for known MS 440 with LAId indicating the same SGSN. If the MS 440 does not have G-CDMA capability, the system manager sends G-CDMA registration (parameter=null) and steps 10 436 and 11 460 are omitted. Note that serving MS 440 with basic IS-707 packet data capability, but without G-CDMA specific capability is not provided by the present invention.

In step 9 436, Registration in the CDMA MSC/VLR 450 is accepted. For G-CDMA subscribers, as noted by the G-CDMA registration message in step 7 432, the BSS manager 410 will wait the acceptance of GPRS procedure at step 11 460 before relaying accept to the MS 440. For regular CDMA user the procedure continues from step 12 462.

In step 10 438, the Location Area Update (LAU) Request is sent to Protocol IW 412 to initiate the appropriate GPRS procedure. The Protocol IW 412 will look at the reg_type parameter to determine which procedure to launch. In step 11 460, when the GPRS procedure is successfully
5 completed, a LA Updating Accept is sent to the BSS manager 410. In step 12 462, when the BSS manager 410 has received both LA Updating Accepts 436 and, if applicable, 640, the Accept is relayed to BSS 442. In step 13 464, the BSS 442 relays the accept on to the MS 440 and the new CDMA system will allocate a new TMSI to the MS.

10 Fig. 5 illustrates the process of a mobile origination call 500 according to the present invention. In Fig. 5, the access interface manager (AIM) is the BSS manager 510 and Protocol IW 512. The inter-system interface manager (IIM) is the system manager 516. In Fig. 5, Mobile Originated packet data call process is shown where there is no initial traffic channel
15 available. The first block of messages 520 represents the packet data call origination. For ease of explanation, only major messages will be explained herein and all messages of Mobile Origination (MO) call are not shown. In step 1-1 522, the origination message with service option set to packet data is sent by the MS 540 to the BSS 542. In step 1-2 524, the CM Service
20 Request is sent by the BSS 542 to the BSS manager 510. In step 1-3 526, the BSS manager 510 checks if the service option is packet data only. If so, optionally BSS manager 510 sends Location Updating Request (reg_type and Auth. Credentials) to MSC/VLR 550 at step 526. The purpose of this message is to use the MSC/VLR 550 to authenticate the MS 540. The

SGSN 518 cannot do authentication, because it will cause a mismatch in the Call History Count. In step 1-4 528, the MSC/VLR 550 performs the Authentication procedure and returns Location Updating Accept message to the BSS manager 510. Finally, in step 1-5 530, the BSS 542 sends CM
5 Service Request to Protocol IW 512.

In step 2, if the Origination included TMSI as the MSId, the Protocol IW 512 will request the IMSI of the MS 540 from the system manager 516 with newly defined Get IMSI 532 and Get IMSI Ack 534 messages. At this point the Protocol IW 512 has to determine if the Origination relates to an
10 existing Packet Data Protocol (PDP) context, or if there is a need to create a new one. If an appropriate PDP context exists already, the procedure may continue from step 7 536. If PDP context needs to be activated, steps 3 560, step 4 562, step 5 564 and step 6 566 take place.

Steps 3.-6 560-566 illustrate a standard GPRS PDP Context
15 activation procedure. A default PDP context is activated as there are no means for the MS 540 to specify the PDP contexts. It is possible to specify the use of the dialed digits as an indication of different types of default PDP contexts, and convert that to GPRS Network Service Access Point Interface (NSAPI) parameter in Protocol IW 512. Optionally the SGSN 518 may
20 initiate the CDMA authentication procedure.

In step 7 536, the Protocol IW 512 sends an Assignment Request message to the BSS 542 through BSS manager 510. Then the "Channel Assignment" process is followed, which can be referred to IS-95 and IS-634.

Figs. 6-8 illustrates a Hard Handoff for speech and packet data according to the present invention. In the G-CDMA system, there are at least nine scenarios of handoff. For ease of explanation, only one scenario will be illustrated herein as an example. Those skilled in the art will
5 recognize that other handoff scenarios are possible. For further ease in explanation, the handoff procedure will be illustrated in Fig. 6-8 as follows.

Fig. 6 illustrates the high level flow of a hard handoff 600 according to the present invention. In Fig. 6, the access interface manager is the BSS manager 610 and the Protocol IW manager 612. The inter-system interface
10 manager is the system manager 616. The discussion herein with reference to Fig. 6 will show only the high level flow, with the details provided in Figs. 7-8.

In Fig. 6, based on the MS 620 reporting that it crossed a network specified threshold for signal strength, the old BSS 622 recommends a hard
15 handoff to one or more cells in the domain of the new BSS 624 and sends a pilot strength measurement signal in step 1 660. Then, Handoff Required and FACDIR2 messages 662 and IS-95 Handoff signaling 664 are sent. The FACDIR2 message is a message which is sent to request a call handoff to a target. In step 2 662, the old BSS 622 sends a Handoff Required
20 Message with CellId List to the MSC 626 to find a target with available resources. Note that the service options are speech and packet data. After IS-95 Handoff signaling 668 and start of GPRS Handoff 670, in step 3 672, the MSC 626 sends a clear command to the old BS 622 indicating the

handoff is to be completed. In step 4 674, the old BS 622 sends a clear complete to the old MSC 626 indicating the completion of the handoff.

Fig. 7 illustrates the Handoff Required and FACDIR2 messaging 700 according to the present invention. In Fig. 7, the access interface manager is the BSS manager 710 and the Protocol IW manager 712. The inter-
5 system interface manager is the System manager 716. In the step-by-step illustration of the Handoff Required and FACDIR2 messaging of Fig. 7, the old BSS 722 recommends a hard handoff to one or more cells in the domain of the new BSS 724 in step 1 760 based on the MS 720 reporting that it
10 crossed a network specified threshold for signal strength. The old BSS 722 sends a Handoff Required Message with CellId List to the old MSC 726 to find a target with available resources. The service options are again speech and packet data.

In step 2 762, the MSC 726 of the regular CDMA system sends a
15 FACDIR2 with service options set to speech plus packet data to the System Manager 716 of the G-CDMA system to invoke the G-CDMA to initiate the handoff. In steps 3 764 and 5 768, the System Manager 716 splits the FACDIR2 into two subsequent FACDIR2 messages: one 764 with service option set to send packet data to the Packet HO Manager 728, and the
20 other one 768 with service option set to send speech to the new CDMA MSC 730.

In steps 4 766 and 6 770, upon receipt the FACDIR2 messages, the Packet HO Manager 728 and new CDMA MSC 730 will separately send HO Request messages to the new BSS Manager 710. The message 766 sent

by the Packet HO Manager 728 is a newly defined message with a new parameter "following service" set to send speech to inform the new BSS Manager 710 that there will be a speech service option requested for handoff subsequently.

5 In step 7 722, the new BSS Manager 710 combines the two HO Request Messages 766, 770 into a single HO Request and sends it to new BSS 724. In step 8 774, the new BSS 724 determines that appropriate resources are available and reserves or allocates traffic channel(s) for speech and packet data services, and sends Handoff Request Ack to new
10 BSS Manager 710. In step 9 776 and 11 780, the new BSS Manager 710 again splits the HO Request Ack into two subsequent messages: one 776 to the Packet HO Manager 728 and the other one 780 to the new CDMA MSC 730. In steps 10 778 and 12 782, upon receipt of the HO Request Ack Messages 776, 780, the Packet HO Manager 728 and the new CDMA MSC
15 730 send facdir2 Messages to the System Manager 716. The HO Request Ack Message 776 and the facdir2 Message 778 sent and received by the Packet HO Manager 728 are newly defined messages which have a new parameter, "following service". In step 13 784, the System Manager 716 combines two facdir2 778, 782 into one facdir2 784 and sends it to the old
20 CDMA MSC 726 to acknowledge FACDIR2 Messages. In step 14 786, upon receipt of the facdir2 Message 784, the old MSC 726 sends a HO Command Message to the old BSS 722 to convey information of the new BSS 724 to the old BSS 722.

Fig. 8 illustrates the start of the GPRS handoff 800 according to the present invention. In Fig. 8, the access interface manager is the BSS manager 810 and the Protocol IW manager 812. The inter-system interface manager is the System manager 816. In the step-by-step illustration of the start of the GPRS handoff 800 of Fig. 8, the new BSS 824 sends an HO Complete Message to the new BSS Manager 810 in step 1 860. In steps 2 862 and 4 866, the new BSS Manager 810 splits the HO Complete Message 860 into two subsequent HO Complete Messages 862, 866 and sends them to the new CDMA MSC 830 and Packet HO Manager 828, separately. In steps 3 864 and 5 868, upon receipt of HO Complete Messages, the new CDMA MSC 830 and Packet HO Manager 828 send a MobileOnChannel Message to the System Manager 816. In step 6 870, the System Manager 816 then combines the two MobileOnChannel Messages 864, 868 into one and sends the combined MobileOnChannel Message 870 to the old CDMA MSC 826 to indicate the handoff has been completed.

In step 7 872, upon receipt of HO Complete Message in step 1 860, the new BSS Manager 810 sends a newly defined Start GPRS HO Message with the MS ID. In step 8 874, if the type of MS ID in step 7 872 is TMSI, the Protocol IW 812 optionally sends a GetIMSI message 874 to the System Manager 816, where GetIMSI is a newly defined message. In step 9 876, the System Manager 816 sends a PARAMREQ message to the old VLR 840 to inquiry IMSI. In step 10 878, the old VLR 840 returns the IMSI to the System Manager 816 by sending paramreq Message. In step 11 880, the

System Manager 816 sends a GetIMSIResponse with the IMSI to Protocol IW 812.

Steps 12.-15 are for the Modified SGSN Routing Area (RA) Update procedures 882, which are not shown. In step 16 890, the Protocol IW 812 sends an Activate PDP Context Request to SGSN 842. In step 17 892, the SGSN 842 sends a Create PDP Context Request Message to the GGSN 844. In step 18 894, the GGSN 844 sends a Create PDP Context Response Message to the SGSN 842. Finally, in step 19 896, the SGSN 842 sends Activate PDP Context Accept to Protocol IW 812.

In summary, the present invention describes an overlay approach to support the implementation of GPRS functionality to an existing network, such as an IS-95 network, without any changes in the existing exchanges. The implementation relies on interface managers implemented between the MSC and the BSS (BSS interface manager), and between the MSC and network side, i.e. other MSCs and the signaling network, wherein this is called the inter-system interface manager. The SGSN of the GPRS network is installed parallel to the MSC, thus having direct interfaces to both interface managers.

The present invention provides an interface that not only has the functionality of protocol conversion, but also some split and combine functionality for messages having significance for both the SGSN and the MSC. As an example, a handover for both packet and circuit switched connections is seen as one procedure in the BSS and in the inter-MSC network. According to the present invention, messages are split in the

interface manager to continue the procedure as two separate processes, packet HO in the SGSN and circuit switched HO in the MSC. Thus, the MSC sees the procedure as circuit switched only HO, and the SGSN as a packet only HO.

5 In addition to the architecture and the splitting combining functionality of the interface managers, the present invention provides an authentication procedure for SGSN, which is performed by triggering a Location Update (LU) in MSC; and as a part of this procedure, the MSC authenticates the MS wherein a successful LU implies successful authentication. TMSI allocation
10 is done by the MSC and the TMSI send by the BSS interface manager to the SGSN. Information about routing areas needed by the SGSNs (e.g., in inter SGSN routing area updates) is generated by the BSS interface manager, and in the existing air interface the routing area information is not transmitted.

15 The foregoing description of the exemplary embodiment of the invention has been presented for the purposes of illustration and description. It is not intended to be exhaustive or to limit the invention to the precise form disclosed. Many modifications and variations are possible in light of the above teaching. It is intended that the scope of the invention be limited not
20 with this detailed description, but rather by the claims appended hereto.

WHAT IS CLAIMED IS:

1. An overlay system provided over an existing switching infrastructure in a wireless communications system for enabling support for high speed services, comprising:

5 a post-second generation infrastructure for providing processing of post-second generation communication services;

a first interface manager, coupled to the post-second generation infrastructure, for providing an access interface to a base station subsystem and processing base station subsystem signaling based upon a type of service and a type of call flow associated with the received signaling from the base station subsystem;

10 a second interface manager, coupled to the post-second generation infrastructure, for providing an inter-system interface to a signaling network and processing inter-system signaling between the signaling network, the first interface manager, the existing switching infrastructure and the post-second generation infrastructure.

2. The overlay system of claim 1 wherein the first interface manager comprises an access interface manager, the access interface manager outputting access interface signaling based on base station subsystem signaling received from the base station subsystem according to a type of service and a type of call flow associated with the received base station subsystem signaling.

3. The overlay system of claim 2 wherein the access interface manager further comprises a base station subsystem manager and a protocol interworking manager.

4. The overlay of claim 3 wherein the second interface further
5 comprises an inter-system interface manager.

5. The overlay of claim 4 wherein the post-second generation infrastructure further comprises a general packet radio service system including a packet handoff manager and a serving general packet radio service support node.

10 6. The overlay of claim 5 wherein the post-second generation infrastructure further comprises a gateway general packet radio service support node coupled to the serving general packet radio service support node.

7. The overlay of claim 6 wherein the inter-system signaling
15 comprises access interface signaling for the access interface manager, post-second generation signaling for the post-second generation switching infrastructure, existing switch signaling for the existing switching infrastructure, and signaling network signaling for the signaling network.

8. The overlay of claim 7 wherein the existing switching
20 infrastructure comprises a mobile switching center and a visitor location register.

9. The overlay of claim 8 wherein the existing switching infrastructure further comprises a home location register coupled to the second interface manager.

10. The overlay of claim 9 wherein the home location register provides administrative information and the current location of each registered subscriber accessing the existing switching infrastructure in the network.

11. The overlay of claim 10 wherein the call flows comprise registration signal flows, mobile origination call flows and hard handoff signal flows.

12. The overlay of claim 1 wherein the access interface manager further comprises a base station subsystem manager and a protocol interworking manager.

13. The overlay of claim 1 wherein the second interface manager further comprises an inter-system interface manager.

14. The overlay of claim 1 wherein the post-second generation infrastructure further comprises a general packet radio service system including a packet handoff manager and a serving general packet radio service support node.

15. The overlay of claim 14 wherein the post-second generation infrastructure further comprises a gateway general packet radio service support node coupled to the serving general packet radio service support node.

5 16. The overlay of claim 1 wherein the inter-system signaling comprises access interface signaling for the access interface manager, post-second generation signaling for the post-second generation switching infrastructure, existing switch signaling for the existing switching infrastructure, and signaling network signaling for the signaling network.

10 17. The overlay of claim 1 wherein the existing switching infrastructure comprises a mobile switching center and a visitor location register.

18. The overlay of claim 17 wherein the existing switching infrastructure further comprises a home location register coupled to the
15 second interface manager.

19. The overlay of claim 18 wherein the home location register provides administrative information and the current location of each registered subscriber accessing the existing switching infrastructure in the network.

20. An overlay system provided over an existing switching infrastructure in a wireless communications system for enabling support for high speed services, comprising:

a post-second generation infrastructure for providing processing of
5 post-second generation communication services;

an access interface manager, coupled to the post-second generation infrastructure, for outputting access interface signaling in response to receiving base station subsystem signaling from the base station subsystem according to a type of service and a type of call flow associated with the
10 received base station subsystem signaling; and

an inter-system interface manager, coupled to the post-second generation infrastructure, the inter-system interface manger including a system manager for processing inter-system signaling between the signaling network, the first interface, the existing switching infrastructure and the post-
15 second generation infrastructure.

21. The overlay of claim 20 wherein the access interface manager further comprises a base station subsystem manager and a protocol interworking manager, and the post-second generation switching infrastructure further comprises a general packet radio service system including a packet handoff manager, and a serving general packet radio service support node coupled to a gateway general packet radio service support node, the base station subsystem manager processing signaling between the existing switching infrastructure, the system manager of the inter-system interface manager and the protocol interworking manager and the packet handoff manager, the protocol interworking manager processing signaling between the system manager of the inter-system interface manager, the packet handoff manager, the base station subsystem manager, and the serving general packet radio service support node.

22. A method for providing post-second generation cellular services without modifying or replacing an existing cellular switching infrastructure, comprising:

providing a post-second generation infrastructure for processing post-
5 second generation communication services;

placing an access interface manager between a public side of switching infrastructures and a base station subsystem, the switching infrastructures comprising the post-second generation infrastructure and the existing switching infrastructure, the access interface manager receiving
10 base station subsystem signaling and outputting access interface signaling based on base station subsystem signaling received from the base station subsystem according to a type of service and a type of call flow associated with the received base station subsystem signaling; and

positioning an inter-system interface manager between the network
15 side of the switching infrastructures and a signaling network, the inter-system interface manager processing inter-system signaling between the signaling network, the access interface manager, the existing switching infrastructure and the post-second generation infrastructure.




Fig. 1





Fig. 2



Inter MSC/VLR Registration




Fig. 4

Mobile Originated Packet Data




Fig. 5




Fig. 6




Fig. 17




Fig. 8



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ :

H04Q 7/24, 7/30

A3

(11) International Publication Number:

WO 00/19742

(43) International Publication Date:

6 April 2000 (06.04.00)

(21) International Application Number: PCT/US99/23002

(22) International Filing Date: 1 October 1999 (01.10.99)

(30) Priority Data:

09/164,554

1 October 1998 (01.10.98)

US

(71)(72) Applicants and Inventors: LE, Khiem [US/US]; 607 St-Andrews Place, Coppell, TX 75019 (US). HSU, Liangchi, Alan [-/US]; 2614 Tillman Drive, Arlington, TX 76006 (US). LANSISALMI, Atte [FI/FI]; Otakallio 4 A 10, FIN-02150 Espoo (FI).

(74) Agent: LYNCH, David, W.; Altera Law Group, 10749 Bren Road East, Minneapolis, MN 55343 (US).


(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published*With international search report.**Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.*

(88) Date of publication of the international search report:

25 May 2000 (25.05.00)

(54) Title: METHOD AND APPARATUS FOR SUPPORTING THIRD GENERATION CELLULAR SERVICES



(57) Abstract

An overlay to an existing cellular switching structure to provide post-second generation services without the need to make modifications or updates to the existing infrastructure is disclosed. The overlay preserves second generation switching while providing post-second generation services. The overlay includes a post-second generation infrastructure for providing processing of post-second generation communication services, a first interface, coupled to the post-second generation infrastructure, for providing an access interface to a base station subsystem and processing base station subsystem signaling based upon a type of service and a type of call flow associated with the received signaling from the base station subsystem, and a second interface, coupled to the post-second generation infrastructure, for providing an inter-system interface to a signaling network and processing inter-system signaling between the signaling network, the first interface, the existing switching infrastructure and the post-second generation infrastructure. The first interface comprises an access interface manager, the access interface manager outputting access interface signaling based on base station subsystem signaling received from the base station subsystem according to a type of service and a type of call flow associated with the received base station subsystem signaling. The access interface manager further comprises a base station subsystem manager and a protocol interworking manager and the second interface includes an inter-system interface manager. The post-second generation infrastructure includes a general packet radio service system including a packet handoff manager, a serving general packet radio service support node, and a gateway general packet radio service support node.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

INTERNATIONAL SEARCH REPORT

In. Application No
PCT/US 99/23002

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 H04Q7/24 H04Q7/30

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 98 32299 A (NOKIA TELECOMMUNICATIONS OY ;KARI HANNU (FI); RAHKONEN PEKKA (FI)) 23 July 1998 (1998-07-23) page 2, line 9 -page 5, line 35 page 8, line 15 -page 10, line 21	1-20

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

Date of the actual completion of the international search

30 March 2000

Date of mailing of the international search report

06/04/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

López-Pérez, M-C

INTERNATIONAL SEARCH REPORT

Information on patent family members

In. .nal Application No

PCT/US 99/23002

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
W0 9832299 A	23-07-1998	FI 970236 A	21-07-1998
		AU 5665298 A	07-08-1998
		EP 0953263 A	03-11-1999
		ZA 9800407 A	03-08-1998



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ :

H04Q 7/24, 7/30

A3

(11) International Publication Number:

WO 00/19742

(43) International Publication Date:

6 April 2000 (06.04.00)

(21) International Application Number: PCT/US99/23002

(22) International Filing Date: 1 October 1999 (01.10.99)

(30) Priority Data:

09/164,554

1 October 1998 (01.10.98)

US

(71)(72) Applicants and Inventors: LE, Khiem [US/US]; 607 St-Andrews Place, Coppell, TX 75019 (US). HSU, Liangchi, Alan [-/US]; 2614 Tillman Drive, Arlington, TX 76006 (US). LANSISALMI, Atte [FI/FI]; Otakallio 4 A 10, FIN-02150 Espoo (FI).

(74) Agent: LYNCH, David, W.; Altera Law Group, 10749 Bren Road East, Minneapolis, MN 55343 (US).


(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published*With international search report.**Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.*

(88) Date of publication of the international search report:

25 May 2000 (25.05.00)

(54) Title: METHOD AND APPARATUS FOR SUPPORTING THIRD GENERATION CELLULAR SERVICES

**(57) Abstract**

An overlay to an existing cellular switching structure to provide post-second generation services without the need to make modifications or updates to the existing infrastructure is disclosed. The overlay preserves second generation switching while providing post-second generation services. The overlay includes a post-second generation infrastructure for providing processing of post-second generation communication services, a first interface, coupled to the post-second generation infrastructure, for providing an access interface to a base station subsystem and processing base station subsystem signaling based upon a type of service and a type of call flow associated with the received signaling from the base station subsystem, and a second interface, coupled to the post-second generation infrastructure, for providing an inter-system interface to a signaling network and processing inter-system signaling between the signaling network, the first interface, the existing switching infrastructure and the post-second generation infrastructure. The first interface comprises an access interface manager, the access interface manager outputting access interface signaling based on base station subsystem signaling received from the base station subsystem according to a type of service and a type of call flow associated with the received base station subsystem signaling. The access interface manager further comprises a base station subsystem manager and a protocol interworking manager and the second interface includes an inter-system interface manager. The post-second generation infrastructure includes a general packet radio service system including a packet handoff manager, a serving general packet radio service support node, and a gateway general packet radio service support node.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

METHOD AND APPARATUS FOR SUPPORTING THIRD GENERATION
CELLULAR SERVICES

BACKGROUND OF THE INVENTION

1. Field of the Invention.

5 This invention relates in general to cellular communication systems,
and more particularly to an overlay to an existing cellular switching structure
to provide post-second generation services without the need to make
modifications or updates to the existing infrastructure.

2. Description of Related Art.

10 The demand by consumers all over the world for mobile
communications continues to expand at a rapid pace and will continue to do
so for at least the next decade. Over 100 million people were using a
mobile service by the end of 1995, and that number is expected to grow to
300 million by the year 2000. Several factors are contributing to the exciting
15 growth in the telecommunications industry. For example, a combination of
technology and competition bring more value to consumers. Phones are
smaller, lighter, had a longer battery life, and are affordable now for the
mass market. Operators are providing excellent voice quality, innovative
services, and roaming across the country or world. Most important, mobility
20 is becoming less expensive for people to use. Around the world, as well as
in the United States, governments are licensing additional spectrum for new
operators to compete with traditional cellular operators. Competition brings
innovation, new services, and lower prices for consumers.

For cellular telephony to continue its spectacular growth, it must handle more subscribers per base station and higher-bandwidth services. Toward that end, the industry's third technology generation (3G) is envisioned as a move beyond voice-only terminals to information
5 communicators that will pass images and data.

Europe's Universal Mobile Telecommunications Standard (UMTS) is the follow-on to the second-generation Global System for Mobile communications (GSM) digital cellular standard. The Universal Mobile Telecommunications System (UMTS) is intended to provide a worldwide
10 standard for personal mobile communications with the mass-market appeal and quality of wireline services. Over recent years, digital cellular technologies, such as GSM, have led the way towards personal communications, making mobile communications available to millions of users all around the world at reasonable cost. But to match the UMTS
15 vision, a communications system must include support for flexible bearer and bandwidth-on-demand services for local (indoor) environments and for wide area coverage; a variety of mixed traffic types and relevant charging capability for mobile multimedia applications; customized services, service creation environments and service flexibility using, for example, intelligent
20 network (IN) tools; and wideband wireless local loop (WLL) enhancement to the fixed network.

However, the wireless market in the United States is not as settled. For example, there are efforts to pursue a third-generation mobile standard based on the CDMA-One air interface.

Accordingly, any post-second generation air interface, e.g., a post-second generation (3G) air interface, must provide high speed packet data and second generation services as a subset of the post-second generation services. Herein post-second generation will be used to referred to any type
5 of entity that is developed and implemented after the second generation entities.

As operators are forced to implement post-second generation infrastructure, second generation switching infrastructure must be modified or replaced to support the new services such as high speed packet data.
10 Still, the framework of the existing infrastructure may not be optimal for support of post-second generation services, and practically, the operator may have to stay with the same switch supplier.

It can be seen that there is a need for a method and system that preserves second generation switching while providing post-second
15 generation services.

It can also be seen that there is a need for an overlay to existing switching infrastructure to provide post-second generation services without requiring modifications or updating to the existing infrastructure.

SUMMARY OF THE INVENTION

To overcome the limitations in the prior art described above, and to overcome other limitations that will become apparent upon reading and understanding the present specification, the present invention discloses an
5 overlay to an existing cellular switching structure to provide post-second generation services without the need to make modifications or updates to the existing infrastructure.

The present invention solves the above-described problems by providing a method and system that preserves second generation switching
10 while providing post-second generation services.

A system in accordance with the principles of the present invention includes a post-second generation infrastructure for providing processing of post-second generation communication services, a first interface manager, coupled to the post-second generation infrastructure, for providing an
15 access interface to a base station subsystem and processing base station subsystem signaling based upon a type of service and a type of call flow associated with the received signaling from the base station subsystem, and a second interface manager, coupled to the post-second generation infrastructure, for providing an inter-system interface to a signaling network
20 and processing inter-system signaling between the signaling network, the first interface manager, the existing switching infrastructure and the post-second generation infrastructure.

Other embodiments of a system in accordance with the principles of the invention may include alternative or optional additional aspects. One

such aspect of the present invention is that the first interface manager comprises an access interface manager, the access interface manager outputting access interface signaling based on base station subsystem signaling received from the base station subsystem according to a type of service and a type of call flow associated with the received base station subsystem signaling.

Another aspect of the present invention is that the access interface manager further comprises a base station subsystem manager and a protocol interworking manager.

Another aspect of the present invention is that the second interface manager further comprises an inter-system interface manager.

Yet another aspect of the present invention is that the post-second generation infrastructure further comprises a general packet radio service system including a packet handoff manager and a serving general packet radio service support node.

Another aspect of the present invention is that the post-second generation infrastructure further comprises a gateway general packet radio service support node coupled to the serving general packet radio service support node.

Another aspect of the present invention is that the inter-system signaling comprises access interface signaling for the access interface manager, post-second generation signaling for the post-second generation switching infrastructure, existing switch signaling for the existing switching infrastructure, and signaling network signaling for the signaling network.

Another aspect of the present invention is that the existing switching infrastructure comprises a mobile switching center and a visitor location register.

Still another aspect of the present invention is that the existing
5 switching infrastructure further comprises a home location register coupled to the second interface.

Another aspect of the present invention is that the home location register provides administrative information and the current location of each registered subscriber accessing the existing switching infrastructure in the
10 network.

Another aspect of the present invention is that the call flows comprise, among others, registration signal flows, mobile origination call flows and hard handoff signal flows.

These and various other advantages and features of novelty which
15 characterize the invention are pointed out with particularity in the claims annexed hereto and form a part hereof. However, for a better understanding of the invention, its advantages, and the objects obtained by its use, reference should be made to the drawings which form a further part hereof, and to accompanying descriptive matter, in which there are illustrated and described
20 specific examples of an apparatus in accordance with the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

Referring now to the drawings in which like reference numbers represent corresponding parts throughout:

Fig. 1 shows an existing second generation cellular architecture;

5 Fig. 2 shows the overview of the infrastructure and overlay according to the present invention;

Fig. 3 illustrates a more detailed block diagram of an overlay system according to the present invention;

10 Fig. 4 illustrates inter-MSC/VLR Registration flow according to the present invention;

Fig. 5 illustrates the flow of a mobile originated packet data according to the present invention;

Fig. 6 illustrates the high level flow of a hard handoff according to the present invention;

15 Fig. 7 illustrates the Handoff Required and FACDIR2 messaging which is used in Fig. 6 according to the present invention; and

Fig. 8 illustrates the start of the GPRS handoff which is used in Fig. 6 according to the present invention.

DETAILED DESCRIPTION OF THE INVENTION

In the following description of the exemplary embodiment, reference is made to the accompanying drawings which form a part hereof, and in which is shown by way of illustration the specific embodiment in which the invention may be practiced. It is to be understood that other embodiments may be utilized as structural changes may be made without departing from the scope of the present invention.

The present invention provides a signaling scheme that includes an overlay to an existing switching infrastructure to provide post-second generation services, without requiring modifications or updating to the existing infrastructure. The overlay scheme according to the present invention involves two primary concepts. The first concept is to combine/split the signaling to/from other switches and to/from the Base Station. The second concept is for the overlay to intercept the signaling between the existing switch and the Base Station, and between the existing switch and the other switches. For clarity purposes only, the present invention will be described with reference to the use of the second generation (2G) IS-95 CDMA air interface as the existing switching infrastructure. However, those skilled in the art will recognize that the present invention is not meant to be limited to a particular existing infrastructure, but preserves the investment in the existing switching infrastructure by continuing to use it for existing services. Furthermore, the overlay can be independently optimized for new services, and does not require a change in the existing second generation infrastructure.

Fig. 1 shows an existing second generation cellular architecture 100.

In Fig. 1, the existing second generation cellular structure includes a base station subsystem (BSS) 110 and the Mobile Switching Center/Visitor Location Register (MSC/VLR) 120. The central component of a network subsystem is the Mobile Switching Center (MSC). The MSC acts like a normal switching node of the Public Switched Telephone Network (PSTN) or Integrated Services Digital Network (ISDN), and additionally provides all the functionality needed to handle a mobile subscriber, such as registration, authentication, location updating, handovers/handoffs, and call routing to a roaming subscriber. The VLR contains selected administrative information from a Home Location Register (HLR), necessary for call control and provision of the subscribed services, for each mobile station (MS) 130 currently located in the geographical area controlled by the VLR. Although each functional entity can be implemented as an independent unit, manufacturers of switching equipment generally implement the VLR together with the MSC, so that the geographical area controlled by the MSC corresponds to that controlled by the VLR, thus simplifying the signaling required.

The switching system interacts with the rest of the world through two interfaces. First, the BSS 110 interacts with the MSC/VLR 120 via the Access Interface 140, e.g., IS-634. Next, the MSC/VLR 120 interacts with the Signaling Network 150 via an Inter-system Interface 160, e.g., IS-41. Finally, the MS 130 interacts with the BSS 110 via an air interface 170, e.g., IS-95.

Fig. 2 shows the overview of the infrastructure and overlay 200. The new mobile station (MS) 210 and new base station subsystem (BSS) 212 support the new post-second generation air interface 214. The existing infrastructure provides second generation services, while the post-second generation infrastructure 230 is designed to support new services in accordance with the new air interface 214. The second generation services could be speech or low speed data service and post-second generation services could be high speed data services or multimedia applications.

The present invention provides an overlay 240 that includes the post-second generation infrastructure 230 as shown in Fig. 2. Two Interface Managers 242, 244 provide functions to combine and split signaling to/from the new BSS 212 and signaling to/from other (switching) systems in the signaling network 260 respectively. By doing so, the existing system 220 is able to provide existing second generation services, which usually are a subset of post-second generation services provided by the post-second generation infrastructure 230. Furthermore, the post-second generation infrastructure 230 for new services can be independently optimized for post-second generation services without changing the existing system 220.

As mentioned above, this invention considers the case of second generation IS-95 CDMA for concreteness, but without loss of generality, although the ideas presented here are applicable to other cases. As IS-95 air interface evolves to a post-second generation interface, i.e. a 3G CDMA air interface, with high speed packet data as the main service driver, the infrastructure is expected to be impacted as follows. The radio base station

(BS) infrastructure will likely have to be replaced by a new one (i.e. CDMA 3G BSS) 212, due to the extensive changes to the radio specifications. The switching infrastructure will also have to be modified to support high speed packet data, although a replacement is less likely. The present invention

5 defines a scheme that enables the addition of an overlay 240 that is optimized for high speed packet data, without requiring changes to the second generation switching infrastructure 220. When it is available, a post-second generation radio base station infrastructure 230 with a standardized access interface can be connected to the second generation switching

10 infrastructure through an Access Interface Manager 242. General Packet Radio Service (GPRS) infrastructure is used in this invention as an example of the post-second generation infrastructure for new services, i.e. GPRS is used to provide high speed packet data for post-second generation services. However, those skilled in the art will recognize that the concept embodied by

15 the present invention can be applied to other systems.

Fig. 2 shows the addition of an overlay 240 on top of the existing switching infrastructure 220 to support post-second generation services. The overlay 240 includes an infrastructure for new services 230, and two interface managers: the Access Interface Manager (AIM) 242, and the Inter-

20 system Interface Manager (IIM) 244. The interface managers 242, 244 perform the appropriate protocol conversions and interworking so that the existing switching infrastructure 220 does not have to be modified, and can still be used for second generation services, which are a subset of the post-second generation services. In particular, the existing switch 220 still sees a

second generation access interface 246 and a second generation inter-system interface 248. The infrastructure investment is thus preserved. The post-second generation BSS 212 sees a post-second generation access interface 250. A standard post-second generation BSS 212 can thus be
5 used. The other post-second generation systems from the signaling network 260 see a post-second generation inter-system interface 252 when they interact with the overlay system 240 and the existing infrastructure 220, thus enabling transparent interoperability. Finally, the protocol conversion/interworking done by the interface managers 242, 244 include
10 two key features: signaling splitting/combining, and signaling interception. Accordingly, the AIM 242 and IIM 244 provide signaling to and from the existing switching system 220, the post-second generation infrastructure 230 and each other, i.e., via inter-manager signaling interface 254.

The AIM 242 provides access interface signaling including the
15 signaling from the AIM 242 to the existing switching system 220 via the second generation access interface 246, signaling 270 from the AIM 242 to the post-second generation infrastructure 230 and inter-manager signaling from the AIM 242 to the IIM 244 via inter-manager interface 254. The IIM processes inter-system signaling including the inter-manager signaling via
20 the inter-manager interface 254, post-second generation signaling 272 for the post-second generation switching infrastructure 230, existing switch signaling via second generation inter-system interface 248, and signaling network signaling for the signaling network via post-second generation inter-system interface 252.

The post-second generation infrastructure 250 for new services can be optimized for new services, independently of the second generation infrastructure 220. While, the existing CDMA system is only suitable for speech and low speed data services, i.e., 9.6 Kbps or 14.4 Kbps maximum, the post-second generation of CDMA is expected to offer high rate services, e.g., 384 Kbps, or very high rate services, e.g., 2 Mbps. Further, while the standardization process of air interface and network for the post-second generation is still underway, the standardization of General Packet Radio Service (GPRS) is almost finalized, and GPRS high speed packet data service is expected to be in service in the near future. Accordingly, the present invention may be applied to the case of overlaying CDMA system and GPRS systems to provide services of speech and high speed packet data in a more timely manner. Accordingly, the more specific explanation of an overlay 240 according to the present invention will be described with reference to a GPRS/CDMA system. Those skilled in the art will recognize that the present invention is not meant to be limited to a GPRS/CDMA system.

Fig. 3 illustrates a more detailed block diagram of an overlay system according to the present invention. In Fig. 3, the 3G CDMA air interface 310 is used between the MS 312 and BSS 314. The existing system includes MSC/VLR 320 and a HLR 382. The HLR 382 contains all the administrative information of each second generation registered subscriber accessing the existing switching infrastructure 320 in the network, along with the current location of a MS 312 requesting second generation mobile services. The

post-second generation infrastructure 330 for new services contains a Packet Handoff (HO) Manager 332 and a Serving GPRS Support Node (SGSN) 334. A Gateway GPRS Support Node (GGSN) 336 is also provided for the GPRS. The Serving GPRS Support Node (SGSN) 334, which is at
5 the same hierarchical level as the MSC 320, keeps track of the individual MS 312 location and performs security functions and access control for packet data services. The GGSN 336 provides interworking with external packet-switched networks, and is connected with SGSNs 334 via an IP-based GPRS backbone network 338.

10 The overlay includes functional entities of an Access Interface Manager (AIM) 340 including a BSS manager 342 and a Protocol Interworking (IW) 342, an Inter-System Interface Manager 350 including a System Manager 352, and a Packet Handoff (HO) Manager 332. In this example, the G-CDMA 360 is the system combining the new air interface
15 310, the existing infrastructure 320, the post-second generation infrastructure 330, and the above-mentioned components of the overlay system. The G-CDMA system 360 is connected to a Signaling System 7 (SS7) signaling network 370. The SS7 signaling network 370 is connected to other systems, such as other G-CDMA systems 380 or a regular, second
20 generation CDMA system 382.

The handling of call flows illustrates the operation, as well as the importance, of the present invention. The present invention may handle all call flows including but not limited to Registration, Mobile Origination Call,

and Hard Handoff (speech and packet data). Figs. 4-6 illustrates examples of call flows according to the present invention.

Fig. 4 illustrates inter-MSC/VLR Registration 400 according to the present invention. In Fig. 4, the access interface manager (AIM) is the BSS manager 410 and Protocol IW 412. The inter-system interface manager (IIM) is the system manager 416. At step 1 418, the MS 440 sends the Registration over the air interface to the BSS 442 indicating the type of registration. At step 2 420, the BSS 442 sends a corresponding access interface message to the BSS manager. At step 3, the BSS manager will routinely distribute a first access interface Registration message 422 (i.e., LA Updating Request) to the MSC/VLR 450 and a second access interface Registration message 424 (i.e., LA Updating Request) to the system manager 416. The message 424 to the system manager 416 will include the Location Area Identity (LAI) of the cell that the MS 440 is registering in. The BSS manager 410 will wait for a response from the system manager 416 to determine whether a GPRS procedure is needed. The system manager 416 will check whether it recognizes this MS 440 or not.

The system manager 416 combines messages 424 at step 3 and the Registration Notification (REGNOT) message at step 4 426 into the REGNOT message at step 5 428. If the MS 440 is not known, the inter-MSC/VLR Registration continues, and the system manager 416 waits to see the HLR updating via step 6 430 for this user. If MS 440 is not known to the MSC/VLR 450, and a Temporary Mobile Subscriber Identification (TMSI)

was used as the Mobile Subscriber Identification (MSId), the IMSI is retrieved. If the MS is known, it is a case of intra-MSC/VLR registration.

In steps 4 426, 5 428, 6 430, and 8 434, the messages are regular IS-41 HLR updating and registration cancellation messages. In step 6 430, the message also carries the GPRS addition in the profile, if one exists, but the system manager 416 will remove the GPRS addition. Message 8 434 contains a pure IS-41 profile. In step 7 432, if the profile has GPRS addition, i.e., the MS is G-CDMA capable, the new G-CDMA registration message is sent to the BSS manager 410. The message in step 7 432 contains a new parameter called the `inter_ind`, which indicates whether the procedure is inter or intra-SGSN. The system manager 416 will indicate "inter SGSN" if the MS 440 is unknown, or known but the LAId indicates another SGSN. The system manager 416 will indicate "intra SGSN" for known MS 440 with LAId indicating the same SGSN. If the MS 440 does not have G-CDMA capability, the system manager sends G-CDMA registration (parameter=null) and steps 10 436 and 11 460 are omitted. Note that serving MS 440 with basic IS-707 packet data capability, but without G-CDMA specific capability is not provided by the present invention.

In step 9 436, Registration in the CDMA MSC/VLR 450 is accepted. For G-CDMA subscribers, as noted by the G-CDMA registration message in step 7 432, the BSS manager 410 will wait the acceptance of GPRS procedure at step 11 460 before relaying accept to the MS 440. For regular CDMA user the procedure continues from step 12 462.

In step 10 438, the Location Area Update (LAU) Request is sent to Protocol IW 412 to initiate the appropriate GPRS procedure. The Protocol IW 412 will look at the reg_type parameter to determine which procedure to launch. In step 11 460, when the GPRS procedure is successfully
5 completed, a LA Updating Accept is sent to the BSS manager 410. In step 12 462, when the BSS manager 410 has received both LA Updating Accepts 436 and, if applicable, 640, the Accept is relayed to BSS 442. In step 13 464, the BSS 442 relays the accept on to the MS 440 and the new CDMA system will allocate a new TMSI to the MS.

10 Fig. 5 illustrates the process of a mobile origination call 500 according to the present invention. In Fig. 5, the access interface manager (AIM) is the BSS manager 510 and Protocol IW 512. The inter-system interface manager (IIM) is the system manager 516. In Fig. 5, Mobile Originated packet data call process is shown where there is no initial traffic channel
15 available. The first block of messages 520 represents the packet data call origination. For ease of explanation, only major messages will be explained herein and all messages of Mobile Origination (MO) call are not shown. In step 1-1 522, the origination message with service option set to packet data is sent by the MS 540 to the BSS 542. In step 1-2 524, the CM Service
20 Request is sent by the BSS 542 to the BSS manager 510. In step 1-3 526, the BSS manager 510 checks if the service option is packet data only. If so, optionally BSS manager 510 sends Location Updating Request (reg_type and Auth. Credentials) to MSC/VLR 550 at step 526. The purpose of this message is to use the MSC/VLR 550 to authenticate the MS 540. The

SGSN 518 cannot do authentication, because it will cause a mismatch in the Call History Count. In step 1-4 528, the MSC/VLR 550 performs the Authentication procedure and returns Location Updating Accept message to the BSS manager 510. Finally, in step 1-5 530, the BSS 542 sends CM
5 Service Request to Protocol IW 512.

In step 2, if the Origination included TMSI as the MSId, the Protocol IW 512 will request the IMSI of the MS 540 from the system manager 516 with newly defined Get IMSI 532 and Get IMSI Ack 534 messages. At this point the Protocol IW 512 has to determine if the Origination relates to an
10 existing Packet Data Protocol (PDP) context, or if there is a need to create a new one. If an appropriate PDP context exists already, the procedure may continue from step 7 536. If PDP context needs to be activated, steps 3 560, step 4 562, step 5 564 and step 6 566 take place.

Steps 3.-6 560-566 illustrate a standard GPRS PDP Context
15 activation procedure. A default PDP context is activated as there are no means for the MS 540 to specify the PDP contexts. It is possible to specify the use of the dialed digits as an indication of different types of default PDP contexts, and convert that to GPRS Network Service Access Point Interface (NSAPI) parameter in Protocol IW 512. Optionally the SGSN 518 may
20 initiate the CDMA authentication procedure.

In step 7 536, the Protocol IW 512 sends an Assignment Request message to the BSS 542 through BSS manager 510. Then the "Channel Assignment" process is followed, which can be referred to IS-95 and IS-634.

Figs. 6-8 illustrates a Hard Handoff for speech and packet data according to the present invention. In the G-CDMA system, there are at least nine scenarios of handoff. For ease of explanation, only one scenario will be illustrated herein as an example. Those skilled in the art will
5 recognize that other handoff scenarios are possible. For further ease in explanation, the handoff procedure will be illustrated in Fig. 6-8 as follows.

Fig. 6 illustrates the high level flow of a hard handoff 600 according to the present invention. In Fig. 6, the access interface manager is the BSS manager 610 and the Protocol IW manager 612. The inter-system interface
10 manager is the system manager 616. The discussion herein with reference to Fig. 6 will show only the high level flow, with the details provided in Figs. 7-8.

In Fig. 6, based on the MS 620 reporting that it crossed a network specified threshold for signal strength, the old BSS 622 recommends a hard
15 handoff to one or more cells in the domain of the new BSS 624 and sends a pilot strength measurement signal in step 1 660. Then, Handoff Required and FACDIR2 messages 662 and IS-95 Handoff signaling 664 are sent. The FACDIR2 message is a message which is sent to request a call handoff to a target. In step 2 662, the old BSS 622 sends a Handoff Required
20 Message with CellId List to the MSC 626 to find a target with available resources. Note that the service options are speech and packet data. After IS-95 Handoff signaling 668 and start of GPRS Handoff 670, in step 3 672, the MSC 626 sends a clear command to the old BS 622 indicating the

handoff is to be completed. In step 4 674, the old BS 622 sends a clear complete to the old MSC 626 indicating the completion of the handoff.

Fig. 7 illustrates the Handoff Required and FACDIR2 messaging 700 according to the present invention. In Fig. 7, the access interface manager is the BSS manager 710 and the Protocol IW manager 712. The inter-system interface manager is the System manager 716. In the step-by-step illustration of the Handoff Required and FACDIR2 messaging of Fig. 7, the old BSS 722 recommends a hard handoff to one or more cells in the domain of the new BSS 724 in step 1 760 based on the MS 720 reporting that it crossed a network specified threshold for signal strength. The old BSS 722 sends a Handoff Required Message with CellId List to the old MSC 726 to find a target with available resources. The service options are again speech and packet data.

In step 2 762, the MSC 726 of the regular CDMA system sends a FACDIR2 with service options set to speech plus packet data to the System Manager 716 of the G-CDMA system to invoke the G-CDMA to initiate the handoff. In steps 3 764 and 5 768, the System Manager 716 splits the FACDIR2 into two subsequent FACDIR2 messages: one 764 with service option set to send packet data to the Packet HO Manager 728, and the other one 768 with service option set to send speech to the new CDMA MSC 730.

In steps 4 766 and 6 770, upon receipt the FACDIR2 messages, the Packet HO Manager 728 and new CDMA MSC 730 will separately send HO Request messages to the new BSS Manager 710. The message 766 sent

by the Packet HO Manager 728 is a newly defined message with a new parameter "following service" set to send speech to inform the new BSS Manager 710 that there will be a speech service option requested for handoff subsequently.

5 In step 7 722, the new BSS Manager 710 combines the two HO Request Messages 766, 770 into a single HO Request and sends it to new BSS 724. In step 8 774, the new BSS 724 determines that appropriate resources are available and reserves or allocates traffic channel(s) for speech and packet data services, and sends Handoff Request Ack to new
10 BSS Manager 710. In step 9 776 and 11 780, the new BSS Manager 710 again splits the HO Request Ack into two subsequent messages: one 776 to the Packet HO Manager 728 and the other one 780 to the new CDMA MSC 730. In steps 10 778 and 12 782, upon receipt of the HO Request Ack Messages 776, 780, the Packet HO Manager 728 and the new CDMA MSC
15 730 send facdir2 Messages to the System Manager 716. The HO Request Ack Message 776 and the facdir2 Message 778 sent and received by the Packet HO Manager 728 are newly defined messages which have a new parameter, "following service". In step 13 784, the System Manager 716 combines two facdir2 778, 782 into one facdir2 784 and sends it to the old
20 CDMA MSC 726 to acknowledge FACDIR2 Messages. In step 14 786, upon receipt of the facdir2 Message 784, the old MSC 726 sends a HO Command Message to the old BSS 722 to convey information of the new BSS 724 to the old BSS 722.

Fig. 8 illustrates the start of the GPRS handoff 800 according to the present invention. In Fig. 8, the access interface manager is the BSS manager 810 and the Protocol IW manager 812. The inter-system interface manager is the System manager 816. In the step-by-step illustration of the start of the GPRS handoff 800 of Fig. 8, the new BSS 824 sends an HO Complete Message to the new BSS Manager 810 in step 1 860. In steps 2 862 and 4 866, the new BSS Manager 810 splits the HO Complete Message 860 into two subsequent HO Complete Messages 862, 866 and sends them to the new CDMA MSC 830 and Packet HO Manager 828, separately. In steps 3 864 and 5 868, upon receipt of HO Complete Messages, the new CDMA MSC 830 and Packet HO Manager 828 send a MobileOnChannel Message to the System Manager 816. In step 6 870, the System Manager 816 then combines the two MobileOnChannel Messages 864, 868 into one and sends the combined MobileOnChannel Message 870 to the old CDMA MSC 826 to indicate the handoff has been completed.

In step 7 872, upon receipt of HO Complete Message in step 1 860, the new BSS Manager 810 sends a newly defined Start GPRS HO Message with the MS ID. In step 8 874, if the type of MS ID in step 7 872 is TMSI, the Protocol IW 812 optionally sends a GetIMSI message 874 to the System Manager 816, where GetIMSI is a newly defined message. In step 9 876, the System Manager 816 sends a PARAMREQ message to the old VLR 840 to inquiry IMSI. In step 10 878, the old VLR 840 returns the IMSI to the System Manager 816 by sending paramreq Message. In step 11 880, the

System Manager 816 sends a GetIMSIResponse with the IMSI to Protocol IW 812.

Steps 12.-15 are for the Modified SGSN Routing Area (RA) Update procedures 882, which are not shown. In step 16 890, the Protocol IW 812 sends an Activate PDP Context Request to SGSN 842. In step 17 892, the SGSN 842 sends a Create PDP Context Request Message to the GGSN 844. In step 18 894, the GGSN 844 sends a Create PDP Context Response Message to the SGSN 842. Finally, in step 19 896, the SGSN 842 sends Activate PDP Context Accept to Protocol IW 812.

10 In summary, the present invention describes an overlay approach to support the implementation of GPRS functionality to an existing network, such as an IS-95 network, without any changes in the existing exchanges. The implementation relies on interface managers implemented between the MSC and the BSS (BSS interface manager), and between the MSC and
15 network side, i.e. other MSCs and the signaling network, wherein this is called the inter-system interface manager. The SGSN of the GPRS network is installed parallel to the MSC, thus having direct interfaces to both interface managers.

The present invention provides an interface that not only has the
20 functionality of protocol conversion, but also some split and combine functionality for messages having significance for both the SGSN and the MSC. As an example, a handover for both packet and circuit switched connections is seen as one procedure in the BSS and in the inter-MSC network. According to the present invention, messages are split in the

interface manager to continue the procedure as two separate processes, packet HO in the SGSN and circuit switched HO in the MSC. Thus, the MSC sees the procedure as circuit switched only HO, and the SGSN as a packet only HO.

5 In addition to the architecture and the splitting combining functionality of the interface managers, the present invention provides an authentication procedure for SGSN, which is performed by triggering a Location Update (LU) in MSC; and as a part of this procedure, the MSC authenticates the MS wherein a successful LU implies successful authentication. TMSI allocation
10 is done by the MSC and the TMSI send by the BSS interface manager to the SGSN. Information about routing areas needed by the SGSNs (e.g., in inter SGSN routing area updates) is generated by the BSS interface manager, and in the existing air interface the routing area information is not transmitted.

15 The foregoing description of the exemplary embodiment of the invention has been presented for the purposes of illustration and description. It is not intended to be exhaustive or to limit the invention to the precise form disclosed. Many modifications and variations are possible in light of the above teaching. It is intended that the scope of the invention be limited not
20 with this detailed description, but rather by the claims appended hereto.

WHAT IS CLAIMED IS:

1. An overlay system provided over an existing switching infrastructure in a wireless communications system for enabling support for high speed services, comprising:

5 a post-second generation infrastructure for providing processing of post-second generation communication services;

a first interface manager, coupled to the post-second generation infrastructure, for providing an access interface to a base station subsystem and processing base station subsystem signaling based upon a type of service and a type of call flow associated with the received signaling from the base station subsystem;

10 a second interface manager, coupled to the post-second generation infrastructure, for providing an inter-system interface to a signaling network and processing inter-system signaling between the signaling network, the first interface manager, the existing switching infrastructure and the post-second generation infrastructure.

2. The overlay system of claim 1 wherein the first interface manager comprises an access interface manager, the access interface manager outputting access interface signaling based on base station subsystem signaling received from the base station subsystem according to a type of service and a type of call flow associated with the received base station subsystem signaling.

3. The overlay system of claim 2 wherein the access interface manager further comprises a base station subsystem manager and a protocol interworking manager.

4. The overlay of claim 3 wherein the second interface further comprises an inter-system interface manager.

5. The overlay of claim 4 wherein the post-second generation infrastructure further comprises a general packet radio service system including a packet handoff manager and a serving general packet radio service support node.

6. The overlay of claim 5 wherein the post-second generation infrastructure further comprises a gateway general packet radio service support node coupled to the serving general packet radio service support node.

7. The overlay of claim 6 wherein the inter-system signaling comprises access interface signaling for the access interface manager, post-second generation signaling for the post-second generation switching infrastructure, existing switch signaling for the existing switching infrastructure, and signaling network signaling for the signaling network.

8. The overlay of claim 7 wherein the existing switching infrastructure comprises a mobile switching center and a visitor location register.

9. The overlay of claim 8 wherein the existing switching infrastructure further comprises a home location register coupled to the second interface manager.

10. The overlay of claim 9 wherein the home location register provides administrative information and the current location of each registered subscriber accessing the existing switching infrastructure in the network.

11. The overlay of claim 10 wherein the call flows comprise registration signal flows, mobile origination call flows and hard handoff signal flows.

12. The overlay of claim 1 wherein the access interface manager further comprises a base station subsystem manager and a protocol interworking manager.

13. The overlay of claim 1 wherein the second interface manager further comprises an inter-system interface manager.

14. The overlay of claim 1 wherein the post-second generation infrastructure further comprises a general packet radio service system including a packet handoff manager and a serving general packet radio service support node.

15. The overlay of claim 14 wherein the post-second generation infrastructure further comprises a gateway general packet radio service support node coupled to the serving general packet radio service support node.

5 16. The overlay of claim 1 wherein the inter-system signaling comprises access interface signaling for the access interface manager, post-second generation signaling for the post-second generation switching infrastructure, existing switch signaling for the existing switching infrastructure, and signaling network signaling for the signaling network.

10 17. The overlay of claim 1 wherein the existing switching infrastructure comprises a mobile switching center and a visitor location register.

18. The overlay of claim 17 wherein the existing switching infrastructure further comprises a home location register coupled to the
15 second interface manager.

19. The overlay of claim 18 wherein the home location register provides administrative information and the current location of each registered subscriber accessing the existing switching infrastructure in the network.

20. An overlay system provided over an existing switching infrastructure in a wireless communications system for enabling support for high speed services, comprising:

a post-second generation infrastructure for providing processing of
5 post-second generation communication services;

an access interface manager, coupled to the post-second generation infrastructure, for outputting access interface signaling in response to receiving base station subsystem signaling from the base station subsystem according to a type of service and a type of call flow associated with the
10 received base station subsystem signaling; and

an inter-system interface manager, coupled to the post-second generation infrastructure, the inter-system interface manger including a system manager for processing inter-system signaling between the signaling network, the first interface, the existing switching infrastructure and the post-
15 second generation infrastructure.

21. The overlay of claim 20 wherein the access interface manager further comprises a base station subsystem manager and a protocol interworking manager, and the post-second generation switching infrastructure further comprises a general packet radio service system including a packet handoff manager, and a serving general packet radio service support node coupled to a gateway general packet radio service support node, the base station subsystem manager processing signaling between the existing switching infrastructure, the system manager of the inter-system interface manager and the protocol interworking manager and the packet handoff manager, the protocol interworking manager processing signaling between the system manager of the inter-system interface manager, the packet handoff manager, the base station subsystem manager, and the serving general packet radio service support node.

22. A method for providing post-second generation cellular services without modifying or replacing an existing cellular switching infrastructure, comprising:

providing a post-second generation infrastructure for processing post-second generation communication services;

placing an access interface manager between a public side of switching infrastructures and a base station subsystem, the switching infrastructures comprising the post-second generation infrastructure and the existing switching infrastructure, the access interface manager receiving base station subsystem signaling and outputting access interface signaling based on base station subsystem signaling received from the base station subsystem according to a type of service and a type of call flow associated with the received base station subsystem signaling; and

positioning an inter-system interface manager between the network side of the switching infrastructures and a signaling network, the inter-system interface manager processing inter-system signaling between the signaling network, the access interface manager, the existing switching infrastructure and the post-second generation infrastructure.




Fig. 1




Fig. 2




Fig. 4 Inter MSC/VLR Registration




Fig. 5 Mobile Originated Packet Data




Fig. 6

CDMA => G-CDMA (packet data & speech)




Fig. 7

Handoff Required & FACDIR2

700





Fig. 8

Start GPRS Handoff

800



INTERNATIONAL SEARCH REPORT

Int. Application No.

PCT/US 99/23002

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 H04Q7/24 H04Q7/30

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 98 32299 A (NOKIA TELECOMMUNICATIONS OY ;KARI HANNU (FI); RAHKONEN PEKKA (FI)) 23 July 1998 (1998-07-23) page 2, line 9 -page 5, line 35 page 8, line 15 -page 10, line 21	1-20

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"Z" document member of the same patent family

Date of the actual completion of the international search

30 March 2000

Date of mailing of the international search report

06/04/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

López-Pérez, M-C

INTERNATIONAL SEARCH REPORT

Information on patent family members

In. .nal Application No

PCT/US 99/23002

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
W0 9832299 A	23-07-1998	FI 970236 A	21-07-1998
		AU 5665298 A	07-08-1998
		EP 0953263 A	03-11-1999
		ZA 9800407 A	03-08-1998

